

FPR P300



Lightweight design

- 60% smaller, 30% lighter



Adapt to extreme environments

- IP63 protection rating
- Charge and discharge at -30°C



Quiet Operation

- Almost 0dB noise within 1000w



Safe and reliable

- UN38.3 certified
- BMS, EMS

FPR P300

Basic Parameters

| | |
|--------------|---------------|
| Capacity | 343Wh, 92.8Ah |
| Output Power | 350W |

Output

| | |
|-------------------|--------------------------------|
| AC | 220V50Hz/110V60Hz/50Hz |
| DC | 12V /6A Max |
| 3 USB-A | 5V/2.4A |
| 1 USB-C | PD3.0 5-20V 100W(Max) |
| 1 Type-C | PD 100W |
| Car Charging Port | 12V/12A Max, support car start |
| LED | 5W, 10W, SOS, Quick flashing |

Input

| | |
|--------------|----------------------------|
| AC | 100V-240V 60/50Hz 2.5A Max |
| DC | 20V/9A 65W |
| PV | 17-24V/6A |
| Car charging | 12.6-15V/100W |
| Solar | 120W Max 3Hours |

Other features

| | |
|-------------------------|-----------------|
| Working Temp -30°C~40°C | -30- 40 |
| Dimensions | 175x140x118(mm) |
| Net weight | 3.5 (Kg) |
| Single gross weight | 4.5 (Kg) |

*Specifications are subject to change without prior notice.